

CONTACT TELEVILT

- **PHONE:** +46 581 171 95
- **E-MAIL GPS:** gps@televilt.se
- **E-MAIL VHF:** vhf@televilt.se

RX-98

SMALL FORMAT - SUPERIOR PERFORMANCE!

The receivers are 2MHz bandwidth receivers (4MHz bandwidth optional) with a built-in scanner capable of scanning 40 different user programmed frequencies.

Power is provided either by 2 AA alkaline batteries (providing approximately 12 hours battery life) or 2 AA rechargeable batteries.

The RX-98 is a very small, lightweight, ergonomically correct telemetry receiver. It is water resistant and designed for one handed operation. The LCD display contains a handy signal strength indicator.

The tracking receiver is delivered in two different versions: RX-98E and RX-98H.

COMMON FEATURES:

- 2 MHz coverage (4 MHz optional).
- Extremely lightweight.
- Scanner to automatically scan up to 40 frequencies.
- Adjustable gain for precise directionality at very close range.
- L.E.D. indicates signal strength and width peak detector.



RX-98E

- Frequency range: 138MHz to 175MHz.
- Weight: 390 grams.
- Size: 146mm x 57mm x 32mm.



RX-98H

- Frequency range: 142MHz to 155MHz.
- Weight: 630 grams (at 142 MHz).
- Size: 240mm x 70mm x 32 mm.
- Built-in foldable tracking antenna.

Refer to Televilt's RX-900 data logger for a receiver with more advanced functions

North and South American customers: Please contact Telemetry Solutions, CA, USA. Phone (925) 798-2373

www.telemetrysolutions.com

